

Tube Glacé - Tige Chromée - Joints NBR											Pression d'utilisation 200 bars							
CODE	ØA	ØB	ØG	Z	E	K	M	J	F	I	D	C	L	H	Force à 200 bars		Pds(Kg)	
DE203005	20	32	40	50	205	35	1/4	32	35	30	16,2	14	13	61	POUSSER 1 608 daN	TIRER 980 daN	1,7	
DE203010				100	255												2	
DE203015				150	305												2,3	
DE203020				200	355												2,6	
DE203025				250	405												2,9	
DE203030				300	455												3,2	
DE203040				400	555												3,8	
DE203050				500	655											4,4		
DE254010	25	40	50	100	270	40	3/8	38	40	35	20,25	18	15	65	POUSSER 2 513 daN	TIRER 1 532 daN	3,23	
DE254015				150	320												3,71	
DE254020				200	370												4,16	
DE254025				250	420												4,66	
DE254030				300	470												5,12	
DE254040				400	570												6,05	
DE254050				500	670												6,99	
DE254060	600	770	7,95															
DE254070	700	870	8,87															
DE254080				800	970											9,82		
DE305010	30	50	60	100	300	43	3/8	42	45	40	25,25	22	40	85	POUSSER 3 927 daN	TIRER 2 513 daN	5,11	
DE305015				150	350												5,74	
DE305020				200	400												6,33	
DE305025				250	450												6,97	
DE305030				300	500												7,6	
DE305040				400	600												8,83	
DE305050				500	700												10,05	
DE305060	600	800	11,27															
DE305070	700	900	12,5															
DE305080				800	1000											13,73		
DE306010	30	60	70	100	300	45	3/8	42	45	40	25,25	22	15	83	POUSSER 5 655 daN	TIRER 4 241 daN	6,3	
DE306015				150	350												6,97	
DE306020				200	400												7,67	
DE306025				250	450												8,31	
DE306030				300	500												8,97	
DE306035				350	550												9,66	
DE306040				400	600												10,36	
DE306045	450	650	10,99															
DE306050	500	700	11,71															
DE306060	600	800	13,03															
DE306070	700	900	14,35															